



US008470051B2

(12) **United States Patent**
Moyer et al.

(10) **Patent No.:** **US 8,470,051 B2**
(45) **Date of Patent:** **Jun. 25, 2013**

(54) **ONE MOTOR FINGER MECHANISM**

(75) Inventors: **Thomas Moyer**, Salt Lake City, UT (US); **Eric L. Faulring**, Albuquerque, NM (US); **Julio J. Santos-Munne**, Glenview, IL (US)

(73) Assignee: **HDT Robotics, Inc.**, Fredericksburg, VA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 86 days.

(21) Appl. No.: **12/965,362**

(22) Filed: **Dec. 10, 2010**

(65) **Prior Publication Data**

US 2011/0144770 A1 Jun. 16, 2011

Related U.S. Application Data

(60) Provisional application No. 61/286,345, filed on Dec. 14, 2009.

(51) **Int. Cl.**
A61F 2/68 (2006.01)

(52) **U.S. Cl.**
USPC **623/64**

(58) **Field of Classification Search**
USPC 623/63-64; 901/32
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,002,585 A 5/1935 Rothwell et al.
2,656,545 A 10/1953 Conzelman
3,751,733 A 8/1973 Fletcher et al.

4,808,187 A 2/1989 Patterson et al.
4,834,443 A 5/1989 Crowder et al.
5,200,679 A 4/1993 Graham
5,246,463 A 9/1993 Giampapa
5,261,266 A 11/1993 Lorenz et al.
5,413,611 A 5/1995 Haslam, II et al.
5,762,390 A 6/1998 Gosselin et al.
5,888,213 A 3/1999 Sears et al.
5,923,139 A 7/1999 Colgate et al.
5,952,796 A 9/1999 Colgate et al.
6,244,644 B1 6/2001 Lovchik et al.
6,471,618 B2 10/2002 Pavlov et al.
6,500,210 B1 12/2002 Sabolich et al.
6,686,911 B1 2/2004 Levin et al.

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2006-281380 10/2006
JP 2009-233790 10/2009
KR 10-0637956 10/2006
WO WO 2009/107164 A1 9/2009

OTHER PUBLICATIONS

W. Book, R. Charles et al. (1996), The concept and implementation of a passive trajectory enhancing robot, International Mechanical Engineering Congress and Exposition, ASME.

(Continued)



Primary Examiner — Bruce E Snow

(74) *Attorney, Agent, or Firm* — Fay Sharpe LLP

(57) **ABSTRACT**

A mechanical finger comprises a plurality of phalanges coupled to a single actuator using a kinematic linkage and a differential linkage arranged in parallel. The mechanical finger is capable of exhibiting consistent predictable motion when moving in free space or when contacting an object at the fingertip, and of curling in order to conform to an object when the contact is at other locations on the finger.

15 Claims, 8 Drawing Sheets



U.S. PATENT DOCUMENTS

6,896,704	B1 *	5/2005	Higuchi et al.	623/64
7,302,296	B1	11/2007	Hoffer	
7,438,724	B2	10/2008	Sears et al.	
2005/0192676	A1	9/2005	Sears et al.	
2006/0012197	A1	1/2006	Anderson et al.	
2007/0038311	A1	2/2007	Kuiken et al.	
2007/0255424	A1	11/2007	Leydet et al.	
2008/0081728	A1	4/2008	Faulring et al.	
2008/0200994	A1	8/2008	Colgate et al.	

OTHER PUBLICATIONS

J. Colgate and J. Brown (1994), Factors Affecting the Z-Width of a Haptic Display, IEEE International Conference on Robotics & Automation, pp. 3205-3210, San Diego, CA.

James E. Colgate, Michael A. Peshkin, and Witaya Wannasuphoprasit, Nonholonomic Haptic Display, Proceedings of the IEEE 1996 International Conference on Robotics and Automation, Philadelphia, PA.

Eric L. Faulring, J. Edward Colgate and Michael A. Peshkin, (2004), a High Performance 6-DOF Haptic Cobot, IEEE International Conference on Robotics and Automation.

Eric Faulring, J. Edward Colgate and Michael A. Peshkin (2005) High Performance Cobotics, IEEE 9th International Conference on Rehabilitation Robotics, Jun. 26, 2005.

R.B. Gillespie, J.E. Colgate, Michael A. Peshkin (2001) A General Framework for Cobot Control, IEEE Transactions on Robotics and Automation, 17(4) p. 391, Aug. 2001.

Carl Moore, Michael A. Peshkin, J. Edward Colgate (2003) Cobot Implementation of Virtual Paths and 3D Virtual Surfaces, IEEE

Transactions on Robotics and Automation, 19(2), p. 347-351, Apr. 2003.

Michael A. Peshkin, J. Edward Colgate, Witaya Wannasuphoprasit, Carl Moore, Brent Gillespie (2001) Cobot Architecture, IEEE Transactions on Robotics and Automation, 17(4), p. 377, Aug. 2001.

R. Brent Gillespie, Carl A. Moore, Michael Peshkin, J. Edward Colgate, Kinematic Creep in a Continuously Variable Transmission; Traction Drive Mechanics for Cobots, Journal of Mechanical Design, Dec. 2002, vol. 124, p. 713-722.

Carl A. Moore, Michael A. Peshkin, J. Edward Colgate Design of a 3R Cobot Using Continuously Variable Transmissions, 1999 International Conference on Robotics and Automation, Detroit, MI.

Greg Paula, Cobots for the Assembly Line, 1997 American Society of Mechanical Engineers, 7 pages.

Carl A. Moore, Continuously Variable Transmission for Serial Link Cobot Architecture, Degree of Masters of Science in Mechanical Engineering, Northwestern University, Mar. 17, 1997, 91 pages.

Singer, Emily; A Prosthetic Arm That Acts Like a Real One; Technology Review, Nov. 27, 2007 (3 pages).

Singer, Emily; Prosthetic Limbs That Can Feel; Technology Review, Nov. 27, 2007 (2 pages).

Jeffrey, Susan; Targeted Muscle Reinnervation Improves Use of Prosthetic Arm; Medscape Medical News, Feb. 8, 2007 (4 pages).

Kuiken, T.A., et al.; The Use of Target Muscle Reinnervation for Improved Myoelectric Prosthesis Control in a Bilateral Shoulder Disarticulation Amputee; a research paper for submission to Prosthetics and Orthotics International, 2004 (16 pages).

International Preliminary Report on Patentability of International Application No. PCT/US2010/059914 dated Jun. 19, 2012 (8 pages).

* cited by examiner




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 7




FIG. 8B




FIG. 6




FIG. 8A

ONE MOTOR FINGER MECHANISM

This application claims the benefit of U.S. provisional patent application No. 61/286,345, filed Dec. 14, 2009, which is incorporated herein by reference for all purposes.

This invention was made with government support under Contract No. N66001-06-C8005, awarded by Defense Advanced Research Projects Agency. The government has certain rights in the invention.

BACKGROUND

A “mechanical finger” refers to an elongated, articulating, mechanical appendage. Like a human finger, a mechanical finger has one end joined to a structure that acts as a base and an opposite end that is not anchored or connected. A mechanical finger used for grasping typically has two or more rigid sections, and preferably at least three, connected end to end by articulating joints. Terminology used to describe the anatomy of a human finger is used to describe a mechanical finger. As in the human finger, each section of the finger is referred to as a “phalanx.” A finger extends from a base and is comprised of at least two, and preferably three, phalanges joined end to end by pivoting or articulating joints. A first articulating joint joins a proximal phalanx to a base, such as a palm of a hand. A second articulating joint joins the proximal phalanx to an intermediate or middle phalanx, and a third articulating joint joins the intermediate phalanx to a distal phalanx. The first joint is referred to as the metacarpophalangeal (MCP) joint, the second as the proximal interphalangeal (PIP) joint, and the third as the distal interphalangeal (DIP) joint.

In a mechanical finger, the phalanges are coupled to one or more motors to cause flexion and extension of the finger. When using a kinematic mechanism for coupling a single motor to the phalanges, the position of the actuator fully determines the position of the joints, but the torque at each joint is unknown. With a differential mechanism, the torque at the actuator determines the torque at each of the driven joints, but neither the velocity nor the position of the individual joints are specified by the actuator velocity or position alone. A kinematic mechanism produces consistent, predictable motion of the finger joints, but it does not allow the finger to curl around an object. Differential mechanisms allow curling and grasping, but often deviate from the desired motion due to forces at the fingertip, causing buckling, or due to friction in the joints, causing undesirable curling behavior when not conforming.

SUMMARY

According to one aspect of an exemplary embodiment of a mechanical finger comprising at least two phalanges driven by a single actuator, and a differential transmits torque in parallel from the actuator to the MCP joint and the PIP joint.

According to another aspect, the mechanical finger further includes a variable stop that limits rotation of the PIP joint based on the angle of rotation of the MCP joint. Such a mechanical finger is capable of exhibiting consistent predictable motion when moving in free space or when contacting an object at the fingertip, and curling in order to conform to an object when the contact is at other locations on the finger.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a schematic illustration of a mechanical finger driven by a single actuator.

FIG. 1B is a schematic illustration of an alternate embodiment of a mechanical finger driven by a single actuator.

FIG. 1C is a schematic illustration of an alternate embodiment of a mechanical finger driven by a single actuator.

FIG. 1D is a schematic illustration of an alternate embodiment of a mechanical finger driven by a single actuator.

FIG. 1E is a schematic illustration of an alternate embodiment of a mechanical finger driven by a single actuator.

FIG. 2 is a perspective view of an example of a prosthetic finger, partially constructed and without a covering, embodying a coupling mechanism according to the principles of the mechanical finger of FIG. 1.

FIG. 3 is an exploded view of the prosthetic finger of FIG. 2.

FIG. 4A is a side view, rendered with perspective, of proximal and medial phalanges of the prosthetic finger of FIG. 2, which is only partially constructed to reveal a differential linkage.

FIG. 4B is a side view, not rendered with perspective, of the partially constructed proximal and medial phalanges of the prosthetic finger of FIG. 2, in an extended position.

FIG. 4C is a side view, not rendered with perspective, of the partially constructed proximal and medial phalanges of the prosthetic finger of FIG. 4B, in a fully flexed position.

FIG. 5A is a side view, rendered with perspective, of proximal and medial phalanges of an alternate embodiment of a prosthetic finger that is partially constructed to reveal a differential linkage.

FIG. 5B is a side view, not rendered with perspective, of the partially constructed proximal and medial phalanges of an alternate embodiment of the prosthetic finger of FIG. 2, in an extended position.

FIG. 5C is a side view, not rendered with perspective, of the partially constructed proximal and medial phalanges of an alternate embodiment of the prosthetic finger of FIG. 5B, in a fully flexed position.

FIG. 6 is a side view, rendered in perspective of proximal and medial phalanges of alternate embodiment of a mechanical finger partially constructed to reveal a differential linkage.

FIG. 7 is a side, perspective view of the partially constructed prosthetic finger of FIG. 2, with certain elements removed to reveal a linkage.

FIG. 8A is a side, non-perspective view of the prosthetic finger of FIG. 2, with several parts removed to illustrate a stop linkage.

FIG. 8B is a perspective view of FIG. 7B.

DETAILED DESCRIPTION

In the following description of a mechanical finger, like numbers refer to like parts.

FIGS. 1A-1E schematically illustrate several alternative embodiments of mechanisms for driving a mechanical finger **100** using a single motor. The mechanism combines a differential, a kinematic linkage and a PIP linkage for coupling the torque and position of a drive output to a mechanical finger **100** having at least two sections in order to control its flexion and extension in a manner that permits it to be used in connection with grasping or other applications in which a curling action is desirable. Such applications include, but are not limited to, robotic hands and prosthetic hands.

The illustrated examples of mechanical finger **100** comprise at least a proximal phalanx **102**, a medial or middle phalanx **104**, and, in the embodiments of FIGS. 1A to 1E, a distal phalanx **106**. “Phalanx” refers to an elongated, rigid section of the finger, and “phalanges” to multiple sections of the finger. The phalanges are sometimes also referred to

herein as first, second and third sections, respectively, of the mechanical finger. Articulating joints, which are not expressly indicated in the figure, permit joined phalanges to pivot with respect to each other around an axis of the joint. The X-axis **108** of the figure represents the angle of extension and flexion of the phalanges relative to each other and to a reference ground **110**. A greater angle indicates flexion of the finger and a smaller angle indicates extension of the finger. The length of arrow **112** represents the angle, designated by the variable Θ_{PF} between the proximal phalanx **102** and a ground **110**. Similarly, the lengths of arrows **114** and **116** represent the relative angles between the proximal phalanx and the middle phalanx, and between the middle phalanx and the distal phalanx, respectively. These angles are designated in the figure by the variables Θ_{MF} and Θ_{DF} , respectively.

The angular position and torque transmitted by an output of a single actuator or drive, which output is represented by line **118**, controls the flexion and extension of the finger. Any type of suitable motor can power the actuator or drive. The type of the motor will depend on the application. The angular position of the output is represented by line **120** and is designated by the variable Θ_m . Torque applied to an object by a joint is represented as a linear force in the figure. The torque delivered by the output of the drive is represented by line **122**. Variable T_m represents the magnitude of the torque from a motor connected to the drive. Note that the motor is not expressly illustrated in the figures. Torque on the metacarpophalangeal (MCP) joint (not shown), designated T_{mcp} , which is generated by force applied to the proximal phalanx, is represented by line **103**. Similarly, torque on the proximal interphalangeal (PIP) joint (not shown) is designated T_{pip} and is represented by line **105**. Torque on the distal interphalangeal (DIP) joint (not shown) is designated T_{dip} and is represented by line **105**.

A hybrid mechanism comprising a kinematic linkage and differential enables conformal grasping by the finger due to the differential, but at the same time curling behavior can be precisely defined during application of forces to the distal phalanx only. In the examples illustrated by the schematics of FIG. 1A-1E, a differential **124** coupled to ground **110** applies the torque T_m from the motor to the proximal phalanx **102**. The differential also applies the torque to linkage **130** in the embodiments of FIGS. 1A, 1B, 1E or to medial phalanx **104** in the two-phalanx embodiment of FIG. 1C, or to a second differential **125** in the embodiment of FIG. 1D. The differential **124** couples the drive output with the MCP joint and the PIP joint. Thus, the drive applies torque to both the PIP and MCP joints in the embodiments of FIGS. 1A-1C and 1E. In the embodiment of FIG. 1D, the combination of differential **124** and differential **125** applies torque applied to the MCP, PIP and DIP joints.

Linkage **130** in FIGS. 1A, 1B, and 1E functions as a kinematic linkage, coupling the motion of PIP and DIP joints through an algebraic relationship. Linkage **130** couples the PIP and DIP joints (not shown), so that both joints rotate together, in a fixed relationship, resulting in the medial and distal phalanges curling together in a natural curling motion. Movement of link **130** relative to the proximal phalanx **102** causes the middle phalanx to rotate about the PIP joint (not shown), and the distal phalanx to rotate with respect to the medial phalanx around the DIP joint (not shown). This coupled curling relative to the proximal phalanx **102** occurs even while motion of proximal phalanx **102** is blocked, such as when conformal grasping is occurring.

As shown in the embodiment illustrated only in FIG. 1B, the linkage **124** may, optionally, include a compliant element **128**, in series with ground, represented in the figure by spring

128. The compliant element is, for example, comprised of an elastic element that generates a spring force. The spring provides compliance for series elasticity and shock mitigation by allowing linkage **124** to stretch a little when forces are applied to it. Elasticity and shock mitigation or dampening can be desirable in certain applications, such as prosthetics. Movement of the linkage **130** relative to the proximal phalanx **102**, such as during curling when the proximal phalanx **102** is blocked, also results in compression of a compliant member represented in the figure by a spring **132** coupled between the proximal phalanx and the link **130**. The spring acts to extend the PIP joint.

Referring only to FIGS. 1A-1D, in each of the illustrated examples a linkage **126** adjusts the position of stop **134** based on rotation of the MCP joint. Stop **134** limits the range of motion of the PIP joint. The linkage sets the position of the hard stop based on the degree of rotation of the MCP joint from ground. Stopping rotation of the PIP joint limits extension of the medial phalanx, as well as the distal phalanx, beyond a predetermined angle relative to the proximal phalanx. The angle of rotation of the MCP joint is represented in the figure as the distance between ground **110** and the proximal phalanx **102**. The angle of the PIP joint relative to the phalanx is indicated by the length of line **114** in the figure. The stop rotates with respect to the PIP joint as the MCP joint rotates, and thus it depends on the angle of the MCP joint. When the proximal phalanges motion is not blocked, the stop linkage **126** enforces natural, simultaneous curling of all three joints, the MCP, PIP and DIP joints. Linkage **126** also enables the finger to resist forces on the distal phalanx without the differential allowing the PIP and DIP joints to straighten and the MCP joint to flex. Despite the system having a differential, the posture of all three joints can thus remain fixed (not against stops) irrespective of the magnitude of a single external force applied to the distal phalanx.

Because of the use of a differential linkage to couple torque from the drive to the MCP and PIP joints, the positions of the MCP and PIP joints are not fully determined by the position of the drive. For any given position of the drive output, the finger mechanism has one free motion available, which is an extension of the proximal phalanx and a flexing of the PIP and DIP joints. Preferably, linkage dimensions and moment arms are chosen so that external forces applied to the finger distal to a point near the fingertip act to straighten the finger, and forces applied proximal to this point act to curl the finger. The point at which the behavior changes from straightening to curling is referenced as the "focal point" of the differential. For external forces that act proximal to the focal point, the MCP joint will extend and the PIP joint will flex.

Referring now to FIGS. 1A-1E, the linkage **126** is also used to move the endpoint for return spring **132**. The return spring **132** acts to straighten the finger and to keep the mechanism pushed over to one side of this free range of motion. In the absence of any external forces pushing on the finger, the return spring makes the finger act as though the differential **124** is not present. The return spring can also provide some resistance to curling of the fingers when forces are applied to the dorsal side of the finger. Any compliance in the differential **124** will result in some motion, but this will occur in all three joints and is not due to the differential coupling.

As illustrated by the embodiment of FIG. 1E, adjustable stop **134** for the PIP joint may be omitted for an application not requiring it, or in which it is desirable not to have it. In this example, the linkage **126** controls only the position of the end point of the PIP joint return spring **132**. The linkage **126** thus becomes a spring centering linkage.

Referring now only to FIG. 1D, this embodiment of a mechanical finger includes a differential **125** comprising differential linkage **136** in place of a kinematic linkage. The differential couples the medial and distal phalanges using a differential relationship. This embodiment also optionally includes an adjustable stop **138** for the DIP joint and return spring **140** for placing a torque on the DIP joint that tends to extend the distal phalanx relative to the medial phalanx. Linkage **142** is connected to proximal phalanx **102** and adjusts the position of DIP stop **138** based on the angle of rotation of the PIP joint. It also sets the endpoint of return spring **140**.

FIGS. 2, 3, 4A-4C, 5A-5C, 6, 7 and 8A-B illustrate various aspects of an exemplary embodiments of mechanical finger **100** for use in a prosthetic application. The prosthesis comprises at least one prosthetic finger **200**. The prosthesis may also include, depending on the needs of the patient, a prosthetic hand, comprising a prosthetic palm to which the mechanical finger is attached, and a prosthetic arm, to which the prosthetic hand is attached. Only the internal structure of the prosthetic finger is illustrated in the figures.

Prosthetic finger **200** is comprised of proximal phalanx **202**, medial phalanx **204**, and distal phalanx **206**. Distal phalanx **206** has been omitted from FIGS. 4A-4F for purposes of illustration. Metacarpophalangeal (MCP) joint **208** connects the finger to a base element, for example, an artificial palm or hand, which is not shown. Proximal interphalangeal (PIP) joint **210** joins the proximal and medial phalanges. Distal interphalangeal (DIP) joint **212** joins the medial and distal phalanges.

In the embodiment shown in FIGS. 3 and 4A-4C, the proximal phalanx **202** houses a differential linkage comprised of a connecting rod **214**, a pivot link **216**, and another connecting rod **218**. Connecting rod **214** is joined by pin **220** to an arm extending from drive output **222**, and thus connects the output drive to one end of the pivot link **216**. Although not shown, a motor—a stepper motor, for example—located in the base element rotates a drive input, which in this example is pin **223**, which in turn rotates the drive output. Drive output **222** is fixed to the pin **223**. Pin **221** joins the connecting rod to the pivot link. Connecting rod **218** connects the other end of the pivot link to plates **228a** and **228b** of the medial phalanx **204**. Pin **224** joins the pivot link to the connecting rod **218**, and pin **226** joins the connecting rod to the plates **228a** and **228b**, which comprise the primary structural elements for medial phalanx **204**.

The midpoint of the pivot link is fixed by pin **230** to plates **232a** and **232b**. The pivot link will rotate within the proximal phalanx, about the axis of pin **230**, as indicated by comparing FIGS. 4B and 4C, when the drive output rotates. During flexion, rotation of the drive output **222** pulls the connecting rod **214**, which pulls on the pivot link **216**, which pulls on a second connecting rod **218**, which pulls on plates **228a** and **228b** of the medial phalanx.

In an alternate embodiment shown in FIGS. 5A-5C, the pivot link **216** (FIGS. 4A-4C) is replaced by an in series compliant element for giving the finger compliance for series elasticity and shock mitigation. In this example, the compliant element comprises spring **217**. Except for the added compliance and elasticity provided by the spring, the differential with spring performs in a substantially similar manner as the pivot link **216**. In another alternate embodiment shown in FIG. 6, the pivot link **216** and the connecting rods **214** and **218** are replaced with a linkage comprising a single connecting rod **219** that is connected by pins **220** and **226** to the drive housing **222** and plate **228b** of the medial phalanx **204**. As can be seen in the figure, the connecting rod must extend beyond the envelope of the proximal phalanx **204**.

In each of the embodiments shown in FIGS. 2 to 8B, plates **228a** and **228b** are the primary structural elements of medial phalanx **204**. Plates **232a** and **232b** are the primary structural elements comprising the proximal phalanx **202**. The differential linkage of FIGS. 4A-4C and 5A-5C described above is housed between the plates. To these plates can be attached shells to give the proximal phalanx its desired exterior shape in the particular prosthetic or other application.

The pins used to join components in the differential linkage, as well as in other linkages described below, permit relative rotation of the joints that are joined. The location of pin **226** is eccentric to the axis of the PIP joint to form a moment arm. The axis of the PIP joint is defined by pin **236**, which pivotally connects the clevis formed by plates **232a** and **232b** of the proximal phalanx with plates **228a** and **228b** of the medial phalanx. For a given rotation of the drive output, either the MCP joint or the PIP joint can rotate. Rotation of the drive output not only applies torque to the MCP joint by causing the pivot link to push against pin **230**, but it also rotates the link, causing the other part of the link to transmit a force that is applied to pin **226**. Even if the proximal phalanx is blocked, the link will nevertheless pivot and apply torque to the PIP joint. Thus, torque from the drive is applied to both the MCP joint and the PIP joint.

Referring now to FIGS. 2, 3, and 7, the medial phalanx **204** houses a kinematic linkage for coupling rotation of the PIP joint to the DIP joint so that both curl simultaneously. The kinematic linkage comprises a connecting rod **238** that spans between the proximal phalanx **202** and the distal phalanx **206**. Pin **240** at a proximal end of the connecting rod engages hole **242** on plate **232b** of the proximal phalanx. Pin **244** on the distal end of the connecting rod engages hole **246** in the distal phalanx. The distal phalanx is linked to the medial phalanx by a hinge formed by pins **248a** and **248b**. These pins cooperate respectively, with a hole on plate **228a** and a hole on plate **228b** of the medial phalanx, and with holes **250a** and **250b** on opposite forks of a clevis extending from a shell forming distal phalanx **252**. Although in this embodiment the linkage is comprised of a single connecting rod, it could comprise multiple links. Furthermore, a differential could be substituted for the kinematic linkage, as described in connection with FIG. 1D.

Referring now only to FIGS. 2, 3, 8A and 8B, the mechanical finger **200** includes, in this embodiment, fixed stop **253** that stops rotation of the PIP joint to prevent hyperextension of the medial phalanx. In this embodiment, a movable PIP stop part **254** rotates on the same axis as the PIP joint to reduce the permitted range of motion of the medial phalanx by limiting further rotation of the PIP joint based on the degree of flexion of the MCP joint. The centerline of pin **236** defines the axis of rotation. The PIP stop part includes a stop portion **255** that interferes with **257** of plate **228a** of the medial phalanx to prevent the medial phalanx from extending. The position of the PIP stop part **254** is based on the degree of rotation of the MCP joint, and is accomplished in this embodiment by a linkage comprising connecting rod **260** between a housing **256** for a drive (not shown) and PIP stop part **254**. The linkage may also be implemented using multiple links. A pin connects the distal end of connecting rod **260** to arm portion **264** of the PIP stop part **254**. The proximal end of connecting rod **260** is connected by another pin to the drive housing **256**. As the MCP joint rotates due to flexion of the proximal phalanx **202**, the connecting rod pulls on the arm **264**, causing the PIP stop part to rotate in the same direction.

With the PIP-stop linkage, the medial phalanx **204** is stopped either by the fixed stop **253** on the proximal phalanx when the proximal phalanx is fully extended, or by the mov-

able stop of PIP-stop part **254** when the MCP joint is rotated during flexion of the proximal phalanx. If the MCP joint rotates, then the PIP joint is forced to rotate as well by the PIP-stop part. During free motion, or when forces are applied to the fingertip, movement of the PIP-stop part helps to produce predictable curling like a fully kinematic mechanism.

In this embodiment, the rotational position of the PIP-stop part **254** also controls the endpoint **270** of the return spring **266**. This spring, which is normally compressed, has the effect of extending the medial phalanx, thus pushing the PIP joint against the PIP-stop. If no external forces act on the finger, the force generated by the spring causes the motion of the finger joints to be controlled by the PIP-stop. If, however, an object blocks the motion of the proximal phalanx, then the differential linkage continues applying torque to the PIP joint, causing PIP and DIP joints to curl and further compressing the return spring.

The kinematic linkage for controlling the position of the PIP stop based on the motion of the MCP joint could also be used to limit or affect the motion of the PIP and DIP joints in other ways. For example, the PIP stop can be removed, permitting the linkage to be used for controlling the end point of the return spring without limiting the motion of the PIP joint.

Although not necessary for operation of the finger as described above, joint positions can be measured using potentiometers coupled with the joints and feedback to a controller for the drive motor in order to drive the finger to desired position, subject to the limitations of being able to do so caused by the differential. Similarly, strain gauges can be placed on, for example, the drive housing **256** to measure torque on the finger and feed the measured torque back to a controller to change the impedance of the finger.

Although the particular components forming the linkages and the phalanges illustrated in FIGS. 2-7 have advantages when used in a prosthetic application, the structures are intended to be illustrative only of the linkage mechanisms illustrated by FIG. 1. These components can be adapted or substituted for when implementing a differential mechanism in parallel with a kinematic mechanism in accordance with FIG. 1. For example, linkages may be replaced with belts or cables or other passive mechanical mechanisms to achieve the same general purpose. Although it is common to use linkages for kinematic mechanisms and cables for differential mechanisms, but either type can be used for either purpose. In addition to being implemented as a linkage, as exemplified by FIGS. 2-8B, the differentials described above may also be implemented using a belt or cable, for example one linking the drive output to a drum or pulley at the PIP joint, a gear train, or a toggle.

Furthermore, applications in which a mechanical finger in accordance with FIGS. 1A-1E can be used include any type of application involving grasping, and include many different types of robotic applications that are not limited to those attempting to mimic a human hand or prosthetic applications. For instance, an anthropomorphic grip may have benefits in many diverse or unstructured or unforeseen contexts just as human hands are so successfully versatile, including industrial grippers, rovers or mobile robots, entertainment, home robots, surgery or minimally invasive surgery, massage, patient transfer or stabilization, and many others.

The foregoing description is of exemplary and preferred embodiments. The invention, as defined by the appended claims, is not limited to the described embodiments. Alterations and modifications to the disclosed embodiments may be made without departing from the invention. The meaning of the terms used in the claims are, unless expressly stated otherwise, intended to have ordinary and customary meaning

and are not intended to be limited to the details of the illustrated structures or the disclosed embodiments.

What is claimed is:

1. An apparatus comprising:

a first member and a second member, the first member coupled between a first and a second joint; the first joint being adapted for coupling to a base element to permit articulation of the first member with respect to the base element;

a differential linkage adapted for receiving torque and for transmitting torque to the first and second joints;

a stop for limiting rotation of the second joint; and

a linkage coupled between the base element and the stop for moving the stop based on the degree of rotation of the first joint.

2. The apparatus of claim 1, further comprising a spring for placing a torque on the second joint in a direction that forces the second member to extend with respect to the first member.

3. The apparatus of claim 2, wherein said stop for limiting rotation of the second, joint is connected to a stop linkage that moves said stop based upon articulation of said first member relative to said base element about said first joint, wherein the spring comprises end point set by the stop linkage.

4. The apparatus of claim 3, wherein the second joint comprises an axis of rotation, and wherein the stop is mounted for rotation about said axis of rotation of the second joint.

5. The apparatus of claim 1, further comprising a third joint and a third member coupled to the third joint, the second member being coupled between the second joint and the third joint.

6. The apparatus of claim 5, further comprising a kinematic linkage for coupling rotation of the second and third joints.

7. A mechanical finger comprising:

a first member, a second member and a third member, the first member coupled between a first and a second joint, the second member coupled between the second joint and a third joint, and the third member coupled to the third joint; the first joint being adapted for coupling to a base element to permit articulation of the first member with respect to the base element;

a differential linkage adapted for receiving torque and for transmitting torque to the first and second joints;

a kinematic linkage for coupling rotation of the second and third joints;

a stop for limiting rotation of the second joint; and

a stop linkage coupled between the base element and the stop for moving the stop based on the degree of rotation of the first joint.

8. The apparatus of claim 7, further comprising a spring for placing a torque on the second joint in a direction that forces the second member to extend with respect to the first member.

9. The apparatus of claim 8, wherein the spring comprises an end point, and wherein the end point of the spring changes location based upon a location of the stop.

10. The apparatus of claim 7, wherein the stop is mounted for rotation about an axis common with the axis of the second joint.

11. A prostheses comprising:

a base portion;

a plurality of fingers, each finger comprising

a first member, a second member and a third member, the first member coupled between a first and a second joint, the second member coupled between the second joint and a third joint, and the third member coupled to the third joint; the first joint being adapted for cou-

9

pling to a base element to permit articulation of the first member with respect to the base element;
 a differential linkage for receiving torque and for transmitting torque to the first and second joints;
 a kinematic linkage for coupling rotation of the second and third joints;
 a stop for limiting rotation of the second joint;
 a stop linkage coupled between the first joint and the stop for moving the stop based on the degree of rotation of the first joint; and
 a spring for placing a torque on the second joint in a direction that forces the second member to extend with respect to the first member.

12. The prosthesis of claim **11**, further comprising a mechanical arm, to which the base portion is attached.

13. An apparatus comprising:

a first member and a second member, the first member coupled between a first and a second joint; the first joint

10

being adapted for coupling to a base element to permit articulation of the first member with respect to the base element;
 a differential linkage adapted for receiving torque and for transmitting torque to the first and second joints;
 a spring for placing a torque on the second joint in a direction that forces the second member to extend with respect to the first member; and
 a linkage coupled between the base element and an endpoint of the spring for moving the endpoint based on the degree of rotation of the first joint.

14. The apparatus of claim **13**, further comprising a third joint and a third member coupled to the third joint, the second member being coupled between the second joint and the third joint.

15. The apparatus of claim **14**, further comprising a kinematic linkage for coupling rotation of the second and third joints.

* * * * *